



Vertical Variable Speed Bandsaw with Stationary Table

MODEL 360

| SPECIFICATION | mm (in.) |
|-------------------------------|---------------------------------------|
| Height Under Guide | 200mm 7-7/8" |
| Throat, Band to Column | 360mm 14-1/8" |
| Blade Speed | 25-117m/min 82-384ft/min |
| Blade Width | 3-13mm 1/8"-1/2" |
| Blade Length | 3025mm 119-1/8" |
| Size of Table | 565×500mm 22-1/4" × 19-5/8" |
| Tilt, Main Table | 15° R, 15° L 10° F, 10° B |
| Motor | 1HP |
| Machine Size | 930×560×1710mm 36-5/8"×22"×67-3/8" |
| Net Weight | 330 kgs 726 lbs |
| Ship Weight | 410 kgs 902 lbs |
| | 1030 × 700 × 1900mm |

Packing Size

40-1/2" × 27-1/2" × 74-3/4"

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, infinitely variable speed, rubber bonded saw wheels & magnetic switches.

OPTIONAL ACCESSORIES:

110 Volt Control & Lighting

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.



Vertical Variable Speed Bandsaw with Auto-Sliding Table

MODEL 360D

| SPECIFICATION | mm (in.) |
|----------------------------------|---|
| Height Under Guide | 165mm 6-1/2" |
| Throat, Band to Column | 360mm 14-1/8" |
| Blade Speed | 25-117m/min 82-384ft/min |
| Blade Width | 3-13mm 1/8"-1/2" |
| Blade Length | 3025mm 119-1/8" |
| Size of Table | 565×500mm 22-1/4"×19-5/8" |
| Tilt, Main Table | 5° R, 5° L |
| Motor | 1HP |
| NO. of "T" Slots in Table | None |
| Table Stroke | 235mm 9-1/4" |
| Table Feed Operation | Electric Powered |
| Machine Size | 930×950×1710mm 36-5/8"×37-3/8"×67-1/4" |
| Net Weight | 350kgs 770lbs |

| | |
|---------------------|--|
| Ship Weight | 430kgs 946lbs |
| Packing Size | 1030×700×1900mm 40-1/2"×27-1/2"×74-3/4" |

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, infinitely variable speed, rubber bonded saw wheels, magnetic switches and electric powered table.

OPTIONAL ACCESSORIES:

110 Volt Control & Lighting

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.

The machine is with a device for automatic linear cutting.

Work table may take speedy reverse movement.

Motion of work table is controlled by stepless speed controller.

Work table is with auto stoppers.

Vertical Variable Speed Bandsaw with Stationary Table

MODEL 400

OPTIONAL ACCESSORY:



Circle Cutting
Attachment



| SPECIFICATION | mm (in.) |
|-------------------------------|--|
| Height Under Guide | 250mm 9-3/4" |
| Throat, Band to Column | 400mm 15-3/4" |
| Blade Speed | 20-376m/min 65-1233ft/min |
| Blade Width | 3-15mm 1/8"-5/8" |
| Blade Length | 3290mm 129-1/2" |
| Size of Table | 600 × 560mm 23-5/8" × 22" |
| Tilt, Main Table | 15° R, 15° L 15° F, 15° B |
| Motor | 2HP |
| Machine Size | 1015 × 630 × 1880mm 40" × 24-3/4" × 74" |
| Net Weight | 550 kgs 1210 lbs |
| Ship Weight | 640 kgs 1408 lbs |
| | 1120 × 800 × 2000mm |

Packing Size

44" × 31-1/2" × 78-3/4"

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, infinitely variable speed, rubber bonded saw wheels, rip fence, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

Circle Cutting Attachment

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.




Vertical Variable Speed Bandsaw with Auto-Sliding Table

MODEL 400D

OPTIONAL ACCESSORIES:



Circle Cutting Attachment



Miter Gauge

| SPECIFICATION | mm (in.) |
|----------------------------------|-------------------------------------|
| Height Under Guide | 215mm 8-1/2" |
| Throat, Band to Column | 400mm 15-3/4" |
| Blade Speed | 20-376m/min 65-1233ft/min |
| Blade Width | 3-15mm 1/8"-5/8" |
| Blade Length | 3300mm 129-7/8" |
| Size of Table | 600×560mm 23-5/8"×22" |
| Tilt, Main Table | 5° R, 5° L |
| Motor | 2HP |
| NO. of "T" Slots in Table | 4 |
| Table Stroke | 260mm 10-1/4" |
| Table Feed Operation | Electric Powered |
| Machine Size | 1015×1040×1880mm 40"×40-7/8"×74" |
| Net Weight | 580kgs 1276lbs |

| | |
|---------------------|--|
| Ship Weight | 670kgs 1474lbs |
| Packing Size | 1010×910×2000mm 39-3/4"×35-7/8"×78-3/4" |

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, 4 "T" slots in table, infinitely variable speed, rubber bonded saw wheels, magnetic switches, electric powered table, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

**Circle Cutting Attachment
Miter Gauge**

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.

The machine is with a device for automatic linear cutting.

Work table may take speedy reverse movement.

Motion of work table is controlled by stepless speed controller.

Work table is with auto stoppers.

Vertical Variable Speed Bandsaw with Stationary Table

MODEL 450



| SPECIFICATION | mm (in.) |
|-------------------------------|--|
| Height Under Guide | 254mm 10" |
| Throat, Band to Column | 450mm 18" |
| Blade Speed | 25-117m/min 82-384ft/min |
| Blade Width | 3-15mm 1/8"-5/8" |
| Blade Length | 3570mm 140-1/2" |
| Size of Table | 565×500mm 22-1/4"×19-5/8" |
| Tilt, Main Table | 15° R, 15° L 10° F, 10° B |
| Motor | 1HP |
| Machine Size | 1030×560×1870mm 40-1/2"×22"×73-5/8" |
| Net Weight | 380kgs 836lbs |
| Ship Weight | 460kgs 1012lbs |
| | 1120×700×2050mm |

Packing Size

44"×27-1/2"×80-3/4"

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, infinitely variable speed, rubber bonded saw wheels & magnetic switches.

OPTIONAL ACCESSORIES:

110 Volt Control Lighting

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.



Vertical Variable Speed Bandsaw with Auto-Sliding Table

MODEL 450D

| SPECIFICATION | mm (in.) |
|----------------------------------|--|
| Height Under Guide | 215mm 8-1/2" |
| Throat, Band to Column | 450mm 18" |
| Blade Speed | 25-117m/min 82-384ft/min |
| Blade Width | 3-15mm 1/8"-5/8" |
| Blade Length | 3570mm 140-1/2" |
| Size of Table | 565×500mm 22-1/4"×19-5/8" |
| Tilt, Main Table | 5° R, 5° L |
| Motor | 1HP |
| NO. of "T" Slots in Table | None |
| Table Stroke | 235mm 9-1/4" |
| Table Feed Operation | Electric Powered |
| Machine Size | 1030×950×1870mm 40-1/2"×37-3/8"×73-5/8" |
| Net Weight | 410kgs 902lbs |

| | |
|---------------------|--|
| Ship Weight | 490kgs 1078lbs |
| Packing Size | 1130×700×2050mm 44-1/2"×27-1/2"×80-3/4" |

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, infinitely variable speed, rubber bonded saw wheels, magnetic switches and electric powered table.

OPTIONAL ACCESSORIES:

110 Volt Control & Lighting

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.

The machine is with a device for automatic linear cutting.

Work table may take speedy reverse movement.

Motion of work table is controlled by stepless speed controller.

Work table is with auto stoppers.


Vertical Variable Speed Bandsaw with Stationary Table

MODEL 500

OPTIONAL ACCESSORIES:



Circle Cutting
Attachment



Miter Gauge

| SPECIFICATION | mm (in.) |
|-------------------------------|--|
| Height Under Guide | 360mm 14-1/8" |
| Throat, Band to Column | 500mm 19-5/8" |
| Blade Speed | 25-456m/min 82-1496ft/min |
| Blade Width | 3-25mm 1/8"-1" |
| Blade Length | 4055mm 159-5/8" |
| Size of Table | 740×680mm 29-1/8"×26-3/4" |
| Tilt, Main Table | 15° R, 15° L 15° F, 15° B |
| Motor | 2HP |
| Machine Size | 1210×730×2050mm 47-5/8"×28-3/4"×80-3/4" |
| Net Weight | 600kgs 1320lbs |
| Ship Weight | 700kgs 1540lbs |
| | 1310×880×2200mm |

Packing Size

51-1/2"×34-5/8"×86-5/8"

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear. grinder, work light, blade guides, chip blower, cleaning brush, infinitely variable speed, rubber bonded saw wheels, thermal overload switches, rip fence, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

**Circle Cutting Attachment
Miter Gauge**

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.


Vertical Variable Speed Bandsaw with Auto-Sliding Table

MODEL 500D

OPTIONAL ACCESSORIES:



Circle Cutting Attachment



Miter Gauge

| SPECIFICATION | mm (in.) |
|----------------------------------|---|
| Height Under Guide | 330mm 12-7/8" |
| Throat, Band to Column | 500mm 19-5/8" |
| Blade Speed | 25-456m/min 82-1496ft/min |
| Blade Width | 3-25mm 1/8"-1" |
| Blade Length | 4070mm 160-1/4" |
| Size of Table | 740×680mm 29-1/8"×26-3/4" |
| Tilt, Main Table | 5° R, 5° L |
| Motor | 2HP |
| NO. of "T" Slots in Table | 4 |
| Table Stroke | 320mm 12-1/2" |
| Table Feed Operation | Electric Powered |
| Machine Size | 1210×1180×2050mm 47-3/8"×46-3/8"×80-3/4" |
| Net Weight | 630kgs 1386lbs |

| | |
|---------------------|--|
| Ship Weight | 730kgs 1606lbs |
| Packing Size | 1130×960×2220mm 44-1/2"×37-3/4"×87-3/8" |

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, 4 "T" slots in table, infinitely variable speed, rubber bonded saw wheels, magnetic switches, electric powered table, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

**Circle Cutting Attachment
Miter Gauge**

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.

The machine is with a device for automatic linear cutting.

Work table may take speedy reverse movement.

Motion of work table is controlled by stepless speed controller.

Work table is with auto stoppers.


Vertical Variable Speed Bandsaw with Stationary Table

MODEL 600

OPTIONAL ACCESSORIES:



Circle Cutting
Attachment



Miter Gauge

| SPECIFICATION | mm (in.) |
|-------------------------------|--|
| Height Under Guide | 304mm 12" |
| Throat, Band to Column | 600mm 24" |
| Blade Speed | 25-456m/min 82-1496ft/min |
| Blade Width | 3-25mm 1/8"-1" |
| Blade Length | 4376mm 172-1/4" |
| Size of Table | 740×680mm 29-1/8"×26-3/4" |
| Tilt, Main Table | 15° R, 15° L 15° F, 15° B |
| Motor | 2HP |
| Machine Size | 1300×770×2060mm 51-1/4"×30-3/8"×81-1/8" |
| Net Weight | 670kgs 1474lbs |
| Ship Weight | 770kgs 1694lbs |
| | 1430×880×2220mm |

Packing Size

56-3/8"×34-5/8"×87-3/8"

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear. grinder, work light, blade guides, chip blower, cleaning brush, infinitely variable speed, rubber bonded saw wheels, thermal overload switches, rip fence, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

**Circle Cutting Attachment
Miter Gauge**

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Manintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.




Vertical Variable Speed Bandsaw with Auto-Sliding Table

MODEL 600D

OPTIONAL ACCESSORIES:



Circle Cutting Attachment



Miter Gauge

| SPECIFICATION | mm (in.) |
|----------------------------------|---|
| Height Under Guide | 274mm 10-3/4" |
| Throat, Band to Column | 600mm 24" |
| Blade Speed | 25-456m/min 82-1496ft/min |
| Blade Width | 3-25mm 1/8"-1" |
| Blade Length | 4376mm 172-1/4" |
| Size of Table | 740×680mm 29-1/8"×26-3/4" |
| Tilt, Main Table | 5° R, 5° L |
| Motor | 2HP |
| NO. of "T" Slots in Table | 4 |
| Table Stroke | 320mm 12-1/2" |
| Table Feed Operation | Electric Powered |
| Machine Size | 1300×1170×2060mm 51-1/8"×46"×81-1/8" |
| Net Weight | 700kgs 1540lbs |

| | |
|---------------------|--|
| Ship Weight | 800kgs 1760lbs |
| Packing Size | 1390×880×2260mm 54-3/4"×34-5/8"×89" |

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, 4 "T" slots in table, infinitely variable speed, rubber bonded saw wheels, magnetic switches, electric powered table, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

**Circle Cutting Attachment
Miter Gauge**

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.

The machine is with a device for automatic linear cutting.

Work table may take speedy reverse movement.

Motion of work table is controlled by stepless speed controller.

Work table is with auto stoppers.


Vertical Variable Speed Bandsaw with Stationary Table

MODEL 700

OPTIONAL ACCESSORIES:



Circle Cutting
Attachment



Miter Gauge

| SPECIFICATION | mm (in.) |
|-------------------------------|--|
| Height Under Guide | 360mm 14-1/8" |
| Throat, Band to Column | 700mm 27-1/2" |
| Blade Speed | 20-394m/min 65-1292ft/min |
| Blade Width | 3-25mm 1/8"-1" |
| Blade Length | 4090mm 161" |
| Size of Table | 740×680mm 29-1/8"×26-3/4" |
| Tilt, Main Table | 15° R, 15° L 15° F, 15° B |
| Motor | 2HP |
| Machine Size | 1420×750×2040mm 55-7/8"×29-1/2"×80-3/8" |
| Net Weight | 700kgs 1540lbs |
| Ship Weight | 800kgs 1760lbs |
| | 1540×930×2100mm |

Packing Size

60-5/8"×36-5/8"×82-5/8"

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, infinitely variable speed, rubber bonded saw wheels, thermal overload switches, rip fence, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

**Circle Cutting Attachment
Miter Gauge**

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.


Vertical Variable Speed Bandsaw with Auto-Sliding Table

MODEL 700D

OPTIONAL ACCESSORIES:



Circle Cutting Attachment



Miter Gauge

| SPECIFICATION | mm (in.) |
|----------------------------------|---|
| Height Under Guide | 325mm 12-5/8" |
| Throat, Band to Column | 700mm 27-1/2" |
| Blade Speed | 20-394m/min 65-1292ft/min |
| Blade Width | 3-25mm 1/8"-1" |
| Blade Length | 4090mm 161" |
| Size of Table | 740×680mm 29-1/8"×26-3/4" |
| Tilt, Main Table | 5° R, 5° L |
| Motor | 2HP |
| NO. of "T" Slots in Table | 4 |
| Table Stroke | 320mm 12-1/2" |
| Table Feed Operation | Electric Powered |
| Machine Size | 1420×1200×2040mm 55-7/8"×47-1/4"×80-3/8" |
| Net Weight | 730kgs 1606lbs |

| | |
|---------------------|--|
| Ship Weight | 830kgs 1826lbs |
| Packing Size | 1340×880×2090mm 52-3/4"×34-5/8"×82-1/4" |

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, 4 "T" slots in table, infinitely variable speed, rubber bonded saw wheels, magnetic switches, electric powered table, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

**Circle Cutting Attachment
Miter Gauge**

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.

The machine is with a device for automatic linear cutting.

Work table may take speedy reverse movement.

Motion of work table is controlled by stepless speed controller.

Work table is with auto stoppers.


Vertical Variable Speed Bandsaw with Stationary Table

MODEL 1000

OPTIONAL ACCESSORIES:



Circle Cutting Attachment



Miter Gauge

| SPECIFICATION | mm (in.) |
|--------------------------------|--|
| Height Under Guide | 360mm 14-1/8" |
| Throat, Band to Column | 1000mm 39-3/8" |
| Blade Speed | 20-394m/min 65-1292ft/min |
| Blade Width | 3-25mm 1/8"-1" |
| Blade Length | 4670mm 183-7/8" |
| Size of Main Table | 740×680mm 29-1/8"×26-7/8" |
| Size of Auxiliary Table | 679×477mm 26-3/4"×18-7/8" |
| Tilt, Main Table | 15° R, 15° L 15° F, 15° B |
| Motor | 2HP |
| Machine Size | 1690×760×1890mm 66-1/2"×29-7/8"×74-3/8" |
| Net Weight | 780kgs 1716lbs |
| | 880kgs |

Ship Weight

1936lbs

Packing Size

1820×910×2100mm

71-5/8"×35-3/4"×82-5/8"

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, infinitely variable speed, rubber bonded saw wheels, thermal overload switches, rip fence, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

Circle Cutting Attachment

Miter Gauge

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.


Vertical Variable Speed Bandsaw with Auto-Sliding Table

MODEL 1000D

OPTIONAL ACCESSORIES:



Circle Cutting Attachment



Miter Gauge

| SPECIFICATION | mm (in.) |
|----------------------------------|---|
| Height Under Guide | 325mm 12-5/8" |
| Throat, Band to Column | 1000mm 39-3/8" |
| Blade Speed | 20-394m/min 65-1292ft/min |
| Blade Width | 3-25mm 1/8"-1" |
| Blade Length | 4670mm 183-7/8" |
| Size of Main Table | 740×680mm 29-1/8"×26-3/4" |
| Size of Auxiliary Table | 679×477mm 26-3/4"×18-3/4" |
| Tilt, Main Table | 5° R, 5° L |
| Motor | 2HP |
| NO. of "T" Slots in Table | 4 |
| Table Stroke | 320mm 12-1/2" |
| Table Feed Operation | Electric Powered |
| Machine Size | 1690×1210×2040mm 66-1/2"×47-5/8"×80-3/8" |

| | |
|---------------------|---|
| Net Weight | 810kgs 1782lbs |
| Ship Weight | 910kgs 2002lbs |
| Packing Size | 1690×1030×2100mm 66-1/2"×40-1/2"×82-5/8" |

STANDARD FEATURES/ACCESSORIES:

Blade welder. shear. grinder. work light, blade guides. chip blower, cleaning brush. rip fence, 4 "T" slots in table, infinitely variable speed, rubber bonded saw wheels, magnetic switches, electric powered table. 110 volt control & lighting.

OPTIONAL ACCESSORIES:

**Circle Cutting Attachment
Miter Gauge**

STANDARD MACHINE FEATURES:

Infinitely variable speed.

The band tension is cushioned.

Blade welder and grinder are front mounted for quick, accurate blade repair and installation.

Interchangeable rubber bonded saw wheels.

Brush for cleaning lower drive wheel.

Maintenance-free airpump provides air to remove chips from the point of cut.

The upper wheel could be adjusted for band tensioning.

Hand wheel controlled speed.

Adjustable saw blade guides.

Machine light is fitted.

Change speeds while the machine is in operation, without stopping, without pulley changes.

Cast iron frame to minimize machine vibration.

The machine is with a device for automatic linear cutting.

Work table may take speedy reverse movement.

Motion of work table is controlled by stepless speed controller.

Work table is with auto stoppers.