

**YSP<sup>®</sup>**

CNC Vertical Lathe Series

*The Power To Turn The World*

CUTTING DIA.

Ø 750

Ø 850

Ø 950

Ø 1000

Ø 1150

Yu Shine Precision Machine Co.,Ltd

封面裡

封底裡

Company Profile

High Rigidity · High Accuracy · Customized

Yu Shine established in 1983 and started from producing varied customized & special purpose machines. We develop & provide a machine for major manufacturers of Motorcycle, Automotive, Aerospace, Ship-building and Heavy Vehicles/Truck in Japan, USA, and Europe.

React to market demand, YSP gradually transfers as CNC vertical lathe manufacturer. Based on customized knowledge and experience in various industries which made YSP became the first Taiwan manufacturer who provides customer full automatic or semi-automatic robot production line in 1989 and turns the high risk, high pollution and high labor jobs to carry by robots.

YSP has a wealth of technical experience to offer customer complete solutions like customized design machines, improving work efficiency, optimizing production line layout, tooling selection, and design special tool holders...etc.

YSP has kept innovating and learning year by year to supply a machine that fulfills the customer requirement and creates profit for the customer, in order to establish win-win cooperation.


Products supplied by YSP has passed CE(European qualified certification), ISO9001(International standardization organization).

Our high precision, high rigidity, and stable quality products are reliable and recognized by worldwide customers and distributors. YSP has references over 56 countries in Germany, Japan, Russia, Italy, the United Kingdom, France, United State...etc. We also participate in major international machine tool exhibitions like Emo, CCMT, JIMTOF, IMTS, and TIMTOS which gain high evolution.

Production & Manufacturing

Why we choose VTL?

- ◆ **Quality Stability**  
Standardization of production
- ◆ **Rapid Delivery**  
Planned Inventory Production
- ◆ **Unique Machine to Meet Demand**  
Customized Design Experience



• Save your cost in designing Fixtures & jigs. • Ring with big diameter and small thickness can be processed as well.



# VLGH Series



Memo \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

[www.yspcnc.com](http://www.yspcnc.com)

## CONTENTS

|       |                                       |
|-------|---------------------------------------|
| 01 02 | Introduction of Models                |
| 03 04 | VLGH Series                           |
| 05 06 | VLGH Series                           |
| 07 08 | Machine Specifications                |
| 09 10 | Main Spindle Output Performance Chart |
| 11    | Tooling System                        |
| 12    | Tooling Interference                  |
| 13    | Axis Travel Diagram                   |
| 14    | Machine Dimensions                    |
| 15 16 | Optional Accessories                  |
| 17 18 | CNC Specificaitons                    |

Machine Intro.

Machine Intro.

|                             |                           |                          |            |           |
|-----------------------------|---------------------------|--------------------------|------------|-----------|
| <b>VLGH</b>                 | <b>750</b>                |                          | <b>ATC</b> | <b>+C</b> |
| Gear Transmission Head Type | Max Turning 0 750-1150 mm | Roller Guide way Box way | ATC        | live tool |




Twin Star Type




Single Type



**Layout Space** Save Space / Good For Aut Production Line Planning





SPECIFICATIONS

**Machine Capacity** VLGH-750R+ATC | VLGH-750R+ATC+C


|                       |       |       |
|-----------------------|-------|-------|
| Max. Swing Diameter   | Ø 900 | Ø 900 |
| Max. Cutting Diameter | Ø 750 | Ø 750 |
| Max. Cutting Height   | 650   | 650   |

**Spindle**

|                          |        |        |
|--------------------------|--------|--------|
| Spindle Nose             | Ø 380  | Ø 380  |
| Spindle Speed            | 5~1100 | 5~1100 |
| Power Tool Spindle Speed | N/A    | 3000   |
| Spindle Bearing I.D.     | Ø 200  | Ø 200  |

**Turret**

|                 |                 |                 |
|-----------------|-----------------|-----------------|
| Turret Type     | BT50            | BT50            |
| Number Of Tools | 12              | 12              |
| Tool Size       | □32 / □25, Ø 50 | □32 / □25, Ø 50 |



SPECIFICATIONS

**Machine Capacity** VLGH-950R+ATC | VLGH-950R+ATC+C



|                       |        |        |
|-----------------------|--------|--------|
| Max. Swing Diameter   | Ø 1000 | Ø 1000 |
| Max. Cutting Diameter | Ø 950  | Ø 950  |
| Max. Cutting Height   | 900    | 900    |

**Spindle**


|                          |         |         |
|--------------------------|---------|---------|
| Spindle Nose             | Ø380    | Ø380    |
| Spindle Speed            | 5 ~ 900 | 5 ~ 900 |
| Power Tool Spindle Speed | N/A     | 3000    |
| Spindle Bearing I.D.     | Ø 260   | Ø 260   |

**Turret**

|                 |                 |                 |
|-----------------|-----------------|-----------------|
| Turret Type     | BT50            | BT50            |
| Number Of Tools | 12              | 12              |
| Tool Size       | □32 / □25, Ø 50 | □32 / □25, Ø 50 |



VLGH-1150HR+ATC/+C



SPECIFICATIONS

**Machine Capacity** VLGH-1150HR+ATC | VLGH-1150HR+ATC+C


|                       |        |        |
|-----------------------|--------|--------|
| Max. Swing Diameter   | Ø 1250 | Ø 1250 |
| Max. Cutting Diameter | Ø 1150 | Ø 1150 |
| Max. Cutting Height   | 900    | 900    |

**Spindle**

|                          |         |         |
|--------------------------|---------|---------|
| Spindle Nose             | Ø520    | Ø520    |
| Spindle Speed            | 5 ~ 600 | 5 ~ 600 |
| Power Tool Spindle Speed | N/A     | 3000    |
| Spindle Bearing I.D.     | Ø 325   | Ø 325   |

**Turret**

|                 |           |           |
|-----------------|-----------|-----------|
| Turret Type     | BT50      | BT50      |
| Number Of Tools | 12        | 12        |
| Tool Size       | □32, Ø 60 | □32, Ø 60 |



VLR-850ATC  
VLR-1000ATC



SPECIFICATIONS

**Machine Capacity** VLR-850ATC | VLR-1000ATC



|                       |        |        |
|-----------------------|--------|--------|
| Max. Swing Diameter   | Ø 1000 | Ø 1200 |
| Max. Cutting Diameter | Ø 850  | Ø 950  |
| Max. Cutting Height   | 800    | 800    |

**Spindle**

|                          |         |        |
|--------------------------|---------|--------|
| Spindle Nose             | A2-11   | A2-15  |
| Spindle Speed            | 20~1500 | 20~600 |
| Power Tool Spindle Speed | N/A     | N/A    |
| Spindle Bearing I.D.     | Ø 220   | Ø 220  |

**Turret**

|                 |                 |                 |
|-----------------|-----------------|-----------------|
| Turret Type     | ATC             | ATC             |
| Number Of Tools | 12              | 12              |
| Tool Size       | □32 / □25, Ø 50 | □32 / □25, Ø 50 |




(Opt.) = Optional N/A = Not Available \* Specifications are subject to change without notice in advance.

|                                | LINEARWAY SERIES  |                   |                   | BOXWAY SERIES     |                   |                   |
|--------------------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Unit                           | VLGH-750R+ATC     | VLGH-750R+ATC+C   | VLGH-950R+ATC     | VLGH-950R+ATC+C   | VLGH-1150HR+ATC   | VLGH-1150HR+ATC+C |
| <b>CAPACITY</b>                |                   |                   |                   |                   |                   |                   |
| Max. Swing Dia. mm             | Ø 900             | Ø 900             | Ø 1100            | Ø 1100            | Ø 1250            | Ø 1250            |
| Max. Cutting Dia. mm           | Ø 750             | Ø 750             | Ø 950             | Ø 950             | Ø 1150            | Ø 1150            |
| Max. Cutting Height mm         | 650               | 650               | 900               | 900               | 900               | 900               |
| <b>SPINDLE</b>                 |                   |                   |                   |                   |                   |                   |
| Spindle Nose                   | Ø 380             | Ø 380             | Ø 380             | Ø 380             | Ø 520             | Ø 520             |
| Spindle Speed rpm              | 5~1100            | 5~1100            | 5~900             | 5~900             | 5~600             | 5~600             |
| Max. Load on Table Nm          | 1500              | 1500              | 2000              | 2000              | 3000              | 3000              |
| Max. Torque kg                 | 4492              | 4492              | 7776              | 7776              | 10968             | 10968             |
| Spindle Bearing I.D. mm        | Ø 200             | Ø 200             | Ø 260             | Ø 260             | Ø 325             | Ø 325             |
| Max.#2 Spindle Speed rpm       | N/A               | 3000              | N/A               | 3000              | N/A               | 3000              |
| <b>ATC</b>                     |                   |                   |                   |                   |                   |                   |
| Turret Type                    | BT50              | BT50              | BT50              | BT50              | BT50              | BT50              |
| Number of Tools pcs            | 12                | 12                | 12                | 12                | 16                | 16                |
| Tool Size mm                   | □32 / □25, Ø 50   | □32, Ø 60         | □32, Ø 60         |
| <b>TRAVEL/FEEDRATE</b>         |                   |                   |                   |                   |                   |                   |
| X Axis Travel mm               | 500               | 500               | 550               | 550               | 700               | 700               |
| Z Axis Travel mm               | 650               | 650               | 900               | 900               | 900               | 900               |
| X Axis Rapid Feedrate m/min    | 20                | 20                | 20                | 20                | 10                | 10                |
| Z Axis Rapid Feedrate m/min    | 20                | 20                | 20                | 20                | 10                | 10                |
| <b>MOTOR</b>                   |                   |                   |                   |                   |                   |                   |
| Spindle Motor (Cont./30min) kw | αP18.5/22         | αP18.5/22         | αP18.5/22         | αP18.5/22         | α37/45/55         | α37/45/55         |
| #2 Spindle Motor kw            | N/A               | 7.5/11            | N/A               | 7.5/11            | N/A               | 7.5/11            |
| X Axis Servo Motor kw          | 3.0               | 3.0               | 7.0               | 7.0               | 7.0               | 7.0               |
| Z Axis Servo Motor kw          | 4.0               | 4.0               | 7.0               | 7.0               | 7.0               | 7.0               |
| Hydraulic Motor kw             | 2.2               | 2.2               | 2.2               | 2.2               | 2.2               | 2.2               |
| Conveyor Motor kw              | 0.2               | 0.2               | 0.2               | 0.2               | 0.2               | 0.2               |
| Coolant Pump kw                | 0.75 + 0.75 + 1.1 | 0.75 + 0.75 + 1.1 | 0.75 + 0.75 + 1.1 | 0.75 + 0.75 + 1.1 | 0.75 + 0.75 + 1.1 | 0.75 + 0.75 + 1.1 |
| <b>OTHER</b>                   |                   |                   |                   |                   |                   |                   |
| 3-Jaw Power Chuck inch         | 24"               | 24"               | 32"               | 32"               | 40"               | 40"               |
| Tool Holder pcs                | Opt.              | Opt.              | Opt.              | Opt.              | Opt.              | Opt.              |
| Tool Collet pcs                | Opt.              | Opt.              | Opt.              | Opt.              | Opt.              | Opt.              |
| <b>MACHINE BODY</b>            |                   |                   |                   |                   |                   |                   |
| Machine(LxW) mm                | 4100x2550         | 4100x2550         | 4200x2900         | 4200x2900         | 4550x2900         | 4550x2900         |
| Machine(H) mm                  | 4380              | 4380              | 4430              | 4430              | 4500              | 4500              |
| Machine Weight kg              | 14000             | 14500             | 16000             | 16500             | 20000             | 21000             |
| Power Requirement kva          | 40                | 45                | 75                | 80                | 75                | 80                |


|                                | BOXWAY & LINEARWAY SERIES |                   |                   |                   |                   |                   |
|--------------------------------|---------------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Unit                           | VLR-750ATC                | VLR-750ATC+C      | VLR-850ATC        | VLR-850ATC+C      | VLR-1000ATC       | VLR-1000ATC+C     |
| <b>CAPACITY</b>                |                           |                   |                   |                   |                   |                   |
| Max. Swing Dia. mm             | Ø 780                     | Ø 780             | Ø 1000            | Ø 1000            | Ø 1200            | Ø 1200            |
| Max. Cutting Dia. mm           | Ø 750                     | Ø 750             | Ø 850             | Ø 850             | Ø 950             | Ø 950             |
| Max. Cutting Height mm         | 650                       | 650               | 800               | 800               | 800               | 800               |
| <b>SPINDLE</b>                 |                           |                   |                   |                   |                   |                   |
| Spindle Nose                   | A2-11                     | A2-11             | A2-11             | A2-11             | A2-15             | A2-15             |
| Spindle Speed rpm              | 50~2000                   | 50~2000           | 20~1500           | 20~1500           | 20~1200           | 20~1200           |
| Spindle Bearing I.D. mm        | Ø 220                     | Ø 220             | Ø 220             | Ø 220             | Ø 220             | Ø 220             |
| Max.#2 Spindle Speed rpm       | N/A                       | 3000              | N/A               | 3000              | N/A               | 3000              |
| <b>TURRET</b>                  |                           |                   |                   |                   |                   |                   |
| Turret Type                    | ATC                       | ATC               | ATC               | ATC               | ATC               | ATC               |
| Number of Tools pcs            | 12                        | 12                | 12                | 12                | 12                | 12                |
| Tool Size mm                   | □32 / □25, Ø 50           | □32 / □25, Ø 50   | □32 / □25, Ø 50   | □32 / □25, Ø 50   | □32 / □25, Ø 50   | □32 / □25, Ø 50   |
| <b>TRAVEL/FEEDRATE</b>         |                           |                   |                   |                   |                   |                   |
| X Axis Travel mm               | 500                       | 550               | 600               | 600               | 645               | 645               |
| Z Axis Travel mm               | 650                       | 650               | 800               | 800               | 800               | 800               |
| X Axis Rapid Feedrate m/min    | 20                        | 20                | 20                | 20                | 20                | 20                |
| Z Axis Rapid Feedrate m/min    | 20                        | 20                | 20                | 20                | 20                | 20                |
| <b>MOTOR</b>                   |                           |                   |                   |                   |                   |                   |
| Spindle Motor (Cont./30min) kw | αP40 (18.5/22)            | αP40 (18.5/22)    | αP40 (18.5/22)    | αP40 (18.5/22)    | α40 (37/45)       | α40 (37/45)       |
| #2 Spindle Motor kw            | N/A                       | α8(7.5/11)        | N/A               | α8(7.5/11)        | N/A               | α8(7.5/11)        |
| X Axis Servo Motor kw          | 3.0                       | 3.0               | 4.0               | 4.0               | 4.0               | 4.0               |
| Z Axis Servo Motor kw          | 4.0                       | 4.0               | 7.0               | 7.0               | 7.0               | 7.0               |
| Hydraulic Motor kw             | 2.2                       | 2.2               | 2.2               | 2.2               | 2.2               | 2.2               |
| Conveyor Motor kw              | 0.2                       | 0.2               | 0.2               | 0.2               | 0.2               | 0.2               |
| Coolant Pump kw                | 0.75 + 0.75 + 1.1         | 0.75 + 0.75 + 1.1 | 0.75 + 0.75 + 1.1 | 0.75 + 0.75 + 1.1 | 0.75 + 0.75 + 1.1 | 0.75 + 0.75 + 1.1 |
| <b>OTHER</b>                   |                           |                   |                   |                   |                   |                   |
| 3-Jaw Power Chuck inch         | 18"                       | 18"               | 24"               | 24"               | 32"               | 32"               |
| Tool Holder pcs                | Opt.                      | Opt.              | Opt.              | Opt.              | Opt.              | Opt.              |
| Tool Collet pcs                | Opt.                      | Opt.              | Opt.              | Opt.              | Opt.              | Opt.              |
| <b>MACHINE BODY</b>            |                           |                   |                   |                   |                   |                   |
| Machine(LxW) mm                | 4200x2550                 | 4280x2650         | 4280x2650         | 4280x2650         | 4280x2800         | 4280x2800         |
| Machine(H) mm                  | 4500                      | 4500              | 4680              | 4680              | 4680              | 4680              |
| Machine Weight kg              | 14000                     | 14500             | 15000             | 15500             | 16000             | 16500             |
| Power Requirement kva          | 40                        | 45                | 45                | 55                | 65                | 75                |

## Main Spindle Output Performance Chart

### VLGH-750ATC Series




- Fanuc-α40/6000ip + Gear box(1/1)
- 18.5/22/26 kw
- 5-1100 rpm (High Speed)




- Fanuc-α40/6000ip + Gear box(1/4)
- 18.5/22/26 kw
- 5-300 rpm (Low Speed)

### VLGH-950ATC Series




- Fanuc-α40/6000ip + Gear box(1/1)
- 18.5/22/26 kw
- 5-900 rpm (High Speed)




- Fanuc-α40/6000ip + Gear box(1/4)
- 18.5/22/26 kw
- 5-333 rpm (Low Speed)

### VLGH-1150ATC Series




- Fanuc-α40/7000i + Gear box(1/1)
- 37/45/55 kw
- 5-600 rpm (High Speed)




- Fanuc-α40/7000i + Gear box(1/4)
- 37/45/55 kw
- 5-292 rpm (Low Speed)

## Main Spindle Output Performance Chart

### VLR-750ATC Series




- Fanuc-α40/6000ip
- 18.5/22/26 kw
- 20-2000 rpm




- Fanuc-α40/6000ip + Gear box(1/1)
- 18.5/22/26 kw
- 20-2000 rpm (High Speed)
- Fanuc-α40/6000ip + Gear box(1/5.5)
- 18.5/22/26 kw
- 20-726 rpm (Low Speed)

### VLR-850ATC Series




- Fanuc-α40/6000ip
- 18.5/22/26 kw
- 20-1500 rpm




- Fanuc-α40/6000ip + Gear box(1/1)
- 18.5/22/26 kw
- 20-1500 rpm (High Speed)
- Fanuc-α40/6000ip + Gear box(1/5.5)
- 18.5/22/26 kw
- 20-300 rpm (Low Speed)

### VLR-1000ATC Series




- Fanuc-α40/6000ip
- 18.5/22/26 kw
- 20-1200 rpm




- Fanuc-α40/6000ip + Gear box(1/1)
- 18.5/22/26 kw
- 20-1200 rpm (High Speed)
- Fanuc-α40/6000ip + Gear box(1/5.5)
- 18.5/22/26 kw
- 20-300 rpm (Low Speed)





ATC Tool Holder



ZAO-32-180 180  
ZAO-32-220 220



ZBO-50-175 175  
ZBO-50-275 275




ZCO-25-210 210  
ZCO-25-360 360


ZDO-25-210 210  
ZDO-25-360 360

ZEO-MT5-210 210  
ZEO-MT6-360 360


ATC +C Tool Holder




ZAC-32-180 180  
ZAC-32-220 220




ZBC-50-175 175  
ZBC-50-275 275




ZCC-25-210 210  
ZCC-25-360 360



ZDC-25-210 210  
ZDC-25-360 360




ZEC-MT5-210 210  
ZEC-MT6-360 360



## Axis Travel Diagram

## Machine Dimensions

### VLGH&VLR Series




|               | A     | B   | C   | D   | E   | F   | G   | H  | I  | J   |
|---------------|-------|-----|-----|-----|-----|-----|-----|----|----|-----|
| VLGH-750 ATC  | Ø 380 | 505 | 130 | 375 | 120 | 93  | 412 | 83 | 10 | 495 |
| VLGH-950 ATC  | Ø 595 | 595 | 130 | 475 | 120 | 93  | 512 | 83 | 10 | 605 |
| VLGH-1150 ATC | Ø 520 | 705 | 130 | 575 | 120 | 93  | 612 | 83 | 10 | 695 |
| VLR-750 ATC   | Ø 380 | 505 | 130 | 375 | 120 | 93  | 412 | 83 | 10 | 495 |
| VLR-850 ATC   | A2-11 | 550 | 170 | 430 | 120 | 133 | 467 | 83 | 50 | 585 |
| VLR-1000 ATC  | A2-15 | 645 | 170 | 475 | 120 | 133 | 512 | 83 | 50 | 595 |


|              | K  | L   | M   | N             | O           | P   | Q  | R   | S   |
|--------------|----|-----|-----|---------------|-------------|-----|----|-----|-----|
| VLGH-750ATC  | 35 | 650 | 145 | 795/758/653   | 193/230/335 | 108 | 45 | 150 | 150 |
| VLGH-950ATC  | 35 | 900 | 145 | 1045/1008/903 | 193/230/335 | 108 | 45 | 150 | 150 |
| VLGH-1150ATC | 35 | 900 | 186 | 1086/1049/944 | 193/230/335 | 149 | 45 | 150 | 150 |
| VLR-750ATC   | 35 | 650 | 145 | 795/758/653   | 193/230/335 | 108 | 45 | 150 | 150 |
| VLR-850 ATC  | 35 | 800 | 175 | 975/938/833   | 193/230/335 | 138 | 45 | 150 | 150 |
| VLR-1000 ATC | 35 | 800 | 175 | 975/938/833   | 193/230/335 | 138 | 45 | 150 | 150 |

### Twin Star Type



|               | L1   | L2  | W1   | W2  | W3   | H1   | H2   | H3   |
|---------------|------|-----|------|-----|------|------|------|------|
| VLGH-750 ATC  | 4100 | 677 | 2550 | 750 | 1500 | 3569 | 4380 | 1094 |
| VLGH-950 ATC  | 4200 | 677 | 2900 | 820 | 1640 | 3620 | 4430 | 1094 |
| VLGH-1150 ATC | 4550 | 725 | 2900 | 700 | 1400 | 3590 | 4500 | 1087 |
| VLR-750 ATC   | 4200 | 677 | 2550 | 750 | 1500 | 3690 | 4500 | 1000 |
| VLR-850 ATC   | 4280 | 677 | 2650 | 600 | 1200 | 3719 | 4680 | 1094 |
| VLR-1000 ATC  | 4280 | 677 | 2800 | 600 | 1200 | 3719 | 4680 | 1094 |

### Single Type



|               | L1   | L2  | W1   | W2  | H1   | H2   | H3   |
|---------------|------|-----|------|-----|------|------|------|
| VLGH-750 ATC  | 4100 | 677 | 2550 | 750 | 3569 | 4380 | 1094 |
| VLGH-950 ATC  | 4200 | 677 | 2900 | 820 | 3620 | 4430 | 1094 |
| VLGH-1150 ATC | 4550 | 725 | 2900 | 700 | 3590 | 4450 | 1087 |
| VLR-750 ATC   | 4200 | 677 | 2550 | 750 | 3590 | 4500 | 1000 |
| VLR-850 ATC   | 4280 | 677 | 2650 | 600 | 3719 | 4680 | 1094 |
| VLR-1000 ATC  | 4280 | 677 | 2800 | 600 | 3719 | 4680 | 1094 |

## Optional Accessories



**A . Tool Pre-Setter**  
Instant tooling measuring.



**B . Probing System for Workpiece**  
Saving operating time.



**C . Linear Scale**  
Resolution 0.001mm.



**D . Magazine**



**E . Siemens CNC Unit**



**F . Air-Conditioner**  
For electric box.



**G . 2 Steps Gear Box**  
Low speed, high torque.



**H . Oilmist Collector**



**I . Full Open Side Door**  
Good for large size componts and auto loading.




**J . Oil Water Separator**



**K . HPC**



**L . Compound Chip Conveyor**



## FANUC CNC 0i-TF Specifications

### STANDARD

#### AXIS CONTROL

|                              |   |
|------------------------------|---|
| 1. Max. Control Feed Axes    | 4 Axes                                  |
| 2. Max. Control Spindle Axes | 2 Axes                                  |
| 3. Axis Synchronous Control  | STD                                     |
| 4. Increment System          | IS-A, IS-B                              |
| 5. Increment System C        | 0.0001 mm<br>0.0001 deg<br>0.00001 inch |
| 6. HRV 3 Control             | STD                                     |
| 7. Inch / Metric Conversion  | STD                                     |
| 8. Interlock                 | STD                                     |
| 9. Machine Lock              | STD                                     |
| 10. Emergency Stop           | STD                                     |
| 11. Overtravel               | STD                                     |
| 12. Mirror Image             | STD                                     |
| 13. Follow Up                | STD                                     |

#### OPERATION

|   |                                   |
|---|-----------------------------------|
| 1. Automatic Operation (Memory)   | STD                               |
| 2. MDI Operation  | STD                               |
| 3. DNC Operation  | STD                               |
| 4. DNC Operation with Memory Card (CF Card and Card Attachment is Required) | STD                               |
| 5. Schedule Function  | STD                               |
| 6. Sequence Number Search   | STD                               |
| 7. Sequence Number Comparison and Stop                                      | STD                               |
| 8. Program Restart  | STD                               |
| 9. Manual Intervention and Return   | STD                               |
| 10. Wrong Operation Prevention  | STD                               |
| 11. Buffer Register   | STD                               |
| 12. Dry Run   | STD                               |
| 13. Single Block  | STD                               |
| 14. Jog Feed  | STD                               |
| 15. Manual Reference Position Return  | STD                               |
| 16. Manual Handle Feed Rate   | $\times 1, \times 10, \times 100$ |

#### ACCURACY COMPENSATION FUNCTION

|   |     |
|---|-----|
| 1. Backlash Compensation  | STD |
| 2. Backlash Compensation for Each Rapid Traverse and Cutting feed | STD |
| 3. Smooth Backlash Compensation                                   | STD |
| 4. Smart Backlash Compensation                                    | STD |

#### INTERPOLATION FUNCTIONS

|   |  |
|---|--|
| 1. Nano Interpolation                   | STD                                      |
| 2. Exat Stop Mode                       | G61                                      |
| 3. Tapping Mode                         | G63                                      |
| 4. Cutting Mode                         | G64                                      |
| 5. Exat Stop                            | G09                                      |
| 6. Linear Interpolation                 | STD                                      |
| 7. Circular Interpolation               | STD                                      |
| 8. Dwell                                | Dwell in Seconds and dwell in revolution |
| 9. Polar Coordinate Interpolation       | STD                                      |
| 10. Cylindrical Interpolation           | STD                                      |
| 11. Thread Cutting, Synchronous Cutting | STD                                      |
| 12. Multi Threading                     | STD                                      |
| 13. Thread Cutting Retract              | STD                                      |
| 14. Continuous Threading                | STD                                      |
| 15. Variable Lead Thread Cutting        | STD                                      |
| 16. Polygon Turning                     | STD                                      |
| 17. Polygon Machining With Two Spindles | STD                                      |
| 18. Skip                                | G31                                      |
| 19. Multi-Step Skip                     | STD                                      |
| 20. High-Speed Skip                     | STD                                      |
| 21. Torque Limit Skip                   | STD                                      |
| 22. Reference Position Return           | G28                                      |
| 23. Reference Position Return Check     | G27                                      |
| 24. 2nd Reference Position Return       | STD                                      |
| 25. 3rd/4th Reference Position Return   | STD                                      |

#### FEED FUNCTION

|  |                     |
|--|---------------------|
| 1. Rapid Traverse Override   | F0 · 25 · 50 · 100% |
| 2. Feed per Minute   | G98                 |
| 3. Feed per Revolution   | G99                 |
| 4. Tangential Speed Constant Control                                     | STD                 |
| 5. Cutting Feedrate Clamp  | STD                 |
| 6. Automatic Acceleration/Deceleration                                   | STD                 |
| 7. Linear Acceleration / Deceleration After Cutting feed Interpolation   | STD                 |
| 8. BeJ-Type Acceleration / Deceleration After Cutting Feed Interpolation | STD                 |
| 9. Feedrate Override   | 0 ~ 150%            |
| 10. Override Cancel  | STD                 |

#### PROGRAM INPUT

|  |                            |
|--|----------------------------|
| 1. Program Code  | EIA / ISO                  |
| 2. Label Skip  | STD                        |
| 3. Parity Check (Horizontal and Vertical Parity)                                 | STD                        |
| 4. Control In/Out  | STD                        |
| 5. Optional Block Skip   | 9                          |
| 6. Max. Programmable Dimension   | $\pm 9$ Digit              |
| 7. Program File Name   | 32 Characters              |
| 8. Sequence Number   | N8 Digit                   |
| 9. Absolute / Incremental Programming  | STD                        |
| 10. Decimal Point Programming / Pocket Calculator Type Decimal Point Programming | STD                        |
| 11. Input Unit 10 time Multiply  | STD                        |
| 12. Diameter/Radius Programming  | STD                        |
| 13. Plane Selection  | G17 · G18 · G19            |
| 14. Rotary Axis Designation  | STD                        |
| 15. Rotary Axis Roll-Over  | STD                        |
| 16. Coordinate System Setting  | STD                        |
| 17. Automatic Coordinate System Setting  | STD                        |
| 18. Workpiece Coordinate System  | G52 ~ G59                  |
| 19. Workpiece Coordinate System Preset   | STD                        |
| 20. Direct Input of Workpiece Origin Offset Value Measured                       | STD                        |
| 21. Manual Absolute On and Off   | STD                        |
| 22. Direct Drawing Dimension Programming   | STD                        |
| 23. G Code System  | A/B/C                      |
| 24. Chamfering / Corner R  | STD                        |
| 25. Programmable Data Input  | G10                        |
| 26. Programmable Parameter Input   | STD                        |
| 27. Sub Program Call   | 10 Folds Nested            |
| 28. Custom Macro   | STD                        |
| 29. Addition of Custom Macro Common Variables                                    | #100 ~ #199<br>#500 ~ #999 |
| 30. Canned Cycle   | STD                        |
| 31. Multiple Repetitive Cycle  | STD                        |
| 32. Multiple repetitive Cycle II (Pocket Profile)                                | STD                        |
| 33. Canned Cycles for Drilling   | STD                        |
| 34. Circular Interpolation by R Programming                                      | RJJ, K 12 Digit            |
| 35. Coordinate System Rotation   | STD                        |
| 36. Pattern Data Input   | STD                        |
| 37. Conversational Programming with Graphic Function                             | STD                        |

#### AUXILIARY / SPINDLE SPEED FUNCTION

|                                      |           |
|--------------------------------------|-----------|
| 1. Constant Surface Speed Control    | STD       |
| 2. Spindle Override                  | 50 ~ 120% |
| 3. Actual Spindle Speed Output       | STD       |
| 4. Spindle Orientation               | STD       |
| 5. Spindle Output Switching Function | STD       |
| 6. Spindle Positioning               | STD       |
| 7. Rapid Tapping                     | STD       |
| 8. M Code Function                   | M2 Digit  |
| 9. S Code Function                   | S5 Digit  |
| 10. T Code Function                  | T4 Digit  |

#### TOOL FUNCTION / TOOL COMPENSATION

|   |                |
|---|----------------|
| 1. Tool Function                                | T7+1/T6+2/T5+3 |
| 2. Tool Offset Pairs                            | 128            |
| 3. Tool Radius / Tool Nose Radius Compensation  | STD            |
| 4. Tool Geometry / Wear Compensation            | STD            |
| 5. Tool Offset Value Counter Input              | STD            |
| 6. Automatic Tool Offset                        | STD            |
| 7. Direct Input of Tool Offset Value Measured   | STD            |
| 8. Direct Input of Tool Offset Value Measured B | STD            |
| 9. Tool Life Management                         | STD            |
| 10. Extended Tool Life Management               | STD            |

#### EDITING OPERATION

|                                    |        |
|------------------------------------|--------|
| 1. Part Program Storage Size       | 1Mbyte |
| 2. Number of Registerable Programs | 800    |
| 3. Part Program Editing            | STD    |
| 4. Extended Part Program Editing   | STD    |
| 5. Program Protect                 | STD    |
| 6. Password Function               | STD    |
| 7. Background Editing              | STD    |
| 8. High Speed Program Management   | STD    |

#### SETTING AND DISPLAY

|                             |     |
|-----------------------------|-----|
| 1. Status Display           | STD |
| 2. Clock Function           | STD |
| 3. Current Position Display | STD |

#### SETTING AND DISPLAY

|  |                            |
|--|----------------------------|
| 4. Program Comment Display                             | Program Name 31 Characters |
| 5. Parameter Setting and Display                       | STD                        |
| 6. Parameter Check Sum Function                        | STD                        |
| 7. Alarm Display                                       | STD                        |
| 8. Alarm History Display                               | STD                        |
| 9. Run Hour and Parts Count Display                    | STD                        |
| 10. Actual Cutting Feedrate Display                    | STD                        |
| 11. Display of Spindle Speed and T Code at All Screens | STD                        |
| 12. Operation Monitor Screen                           | STD                        |
| 13. Maintenance Information Screen                     | STD                        |
| 14. Trouble Diagnosis                                  | STD                        |
| 15. Multi - Language Display                           | 25 Kinds                   |
| 16. Data Protection Key                                | STD                        |
| 17. Erase CRT Screen Display                           | Manual or Automatic        |
| 18. Parameter Setting Support Screen                   | STD                        |
| 19. Help Function                                      | STD                        |
| 20. Self - Diagnosis Function                          | STD                        |
| 21. Periodic Maintenance Screen                        | STD                        |
| 22. Servo Information Screen                           | STD                        |
| 23. Spindle Information Screen                         | STD                        |
| 24. Graphic Display                                    | STD                        |

#### DATA INPUT / OUTPUT

|                               |        |
|-------------------------------|--------|
| 1. Memory Card Input / Output | STD    |
| 2. Interface                  | RS-232 |
| 3. External Workpiece Number  | 9999   |
| 4. Automatic Data Backup      | STD    |

#### INTERFACE FUNCTION

|  |     |
|--|-----|
| 1. Ethernet                            | STD |
| 2. Enhanced Embedded Ethernet Function | STD |

### OPTIONAL

|                              |         |
|------------------------------|---------|
| 1. Manual Guide Function     |         |
| 2. Part Program Storage Size | 2 Mbyte |